

Soft seated check valve with rubberlined disc, low maintenance, with free passage, for potable water and wastewater pipes and building and industrial plants

Futures:

- Face to Face acc. EN 558-1 series 48 (DIN 3202/F6)
- Size: DN50 to DN500
- Flange connection acc. DIN EN 1092-2 PN10-16
- Easy maintenance without dismantling from the pipeline
- Rubberlined disc
- Horizontal and vertical installation (flow direction upwards)
- The built-in stem enables a lever and a weight to be fitted
- With free passage



Material

- **Body, bonnet:**
 - ✚ EN-GJS-400-15 (GGG-40)
Other materials on request
- **Rubberlined disc:**
 - ✚ EN-GJS-400-15 (GGG-40)
EPDM rubberlined
 - ✚ EN-GJS-400-15 (GGG-40)
NBR rubberlined
Other materials on request
- **Stem:**
 - ✚ 1.4021 (Stainless Steel)
 - ✚ 1.4571 (Stainless Steel)
Other materials on request
- **Bolts:**
 - ✚ Stainless Steel
Other materials on request

Corrosion protection

- *In- and Outside fusion bonded epoxy, RAL5015 skyblue
Acc. to DIN 30677-2 and EN14901
Other coating systems an RAL colors on request*

Application:

- *Water management*
- *Industry*
- *Building technology*

Accessories:

- *Lever and weight
In the standard version on the left in the direction of flow
(optionally on the right in the direction of flow)*
- *Protective cage (steel, fusion bonded epoxy RAL7037)*
- *Pressure gauge connections*
- *Lifting device*
- *PN 6 flanges*