

Soft seated check valve with rubber disc, low maintenance, with free passage, for drinking water and wastewater pipes and building and industrial plants

Futures:

- Face to Face acc. EN 558-1 Line 48 (DIN 3202/F6)
- Size: DN40 to DN500
- Flange connection acc. DIN EN 1092-2 PN10-PN16
- Easy maintenance without dismantling from the pipeline
- Double lifetime due to turnable disc (up to DN300)
- Horizontal and vertical installation (flow direction upwards)
- Quiet operation
- With free passage



Material

- **Body:**
 - ✚ EN-JS 1030 (GGG 40)
other materials on request
- **Disc:**
 - ✚ EN-JS 1030 (GGG 40)
other materials on request
- **Disc gumming:**
 - ✚ EPDM KTW
 - ✚ NBR
other materials on request
- **Shaft:**
 - ✚ stainless steel
other materials on request
- **Bolts:**
 - ✚ stainless steel
other materials on request

Corrosion protection:

- *In- and Outside fusion bonded epoxy, RAL5015 skyblue
Acc. to DIN 30677-2 and EN14901
other coating systems and RAL colors on request*

Application:

- *Water management*
- *Industry*
- *Process engineering*

Accessuories:

- *Lifting device*
- *Manometer connections*
- *PN 6 flanges*

Our approvals

